



An Experimental Investigation Studying the Influence of Dimples on a Film Cooled Turbine Blade Leading Edge

By Paul G. Frisinger

Biblioscholar Okt 2012, 2012. Taschenbuch. Book Condition: Neu. 246x189x10 mm. This item is printed on demand - Print on Demand Neuware - An investigation was conducted to examine the effect of a row of cylindrical surface dimples in reducing the heat load on a turbine blade leading edge model. The models consisted of a foam cylindrical leading edge with a flat afterbody fabricated from Plexiglass. A single coolant hole was located 21.5- from the leading edge, angled 20- to the surface and 90- from the streamwise direction. The leading edge diameter to hole diameter ratio was $D/d = 18.7$. A row of seven dimples was placed upstream of one of the coolant holes. Infrared thermography techniques were used to determine the adiabatic effectiveness, and heat transfer coefficient, h , distributions so that the net heat flux reduction could be calculated. Freestream conditions consisted of Reynolds numbers of 60,000 and 30,000 at both low turbulence and high turbulence. 174 pp. Englisch.



READ ONLINE

[4.4 MB]

Reviews

The best publication i actually study. It is probably the most awesome ebook i actually have study. You are going to like the way the article writer publish this publication.

-- Ms. Harmony Simonis I

Totally among the best publication I have ever go through. This really is for all those who statte that there had not been a well worth studying. I am just very happy to let you know that this is actually the very best pdf we have go through inside my very own daily life and could be he very best ebook for actually.

-- Miss Audra Moen